Ristoattrezzature®

Cod: 7410

Energy-efficient stainless steel refrigerated display cabinet with 4 glass doors, -2 to +8 °C, 223×70×85h cm



Description

Energy-efficient refrigerated display cabinet with containers compliant with catering regulations. Internal and external structure in stainless steel. ‘Embraco’ compressor rated for tropical conditions up to +43°C. ‘Dixell’ digital thermostat. ‘EBM’ forced-air cooling. Corrosion-resistant evaporator. Automatic defrost. Adjustable steel feet supplied as standard. Rounded internal corners for easy cleaning. Self-closing door. Magnetic seals, easy to clean and replace. Compatible with GN sizes. Shelves, guides and castors available as accessories.

Dimensions

External dimensions	2230x700x850 mm
Grid dimensions	330x555 mm
Insulation thickness	60 mm
Internal dimensions	1692x570x580 mm

Technical specifications

Capacity	560 Lt
Compressor	Embraco EM2X3121U
Defrosting	air defrost
Electrical Power	0.4 kW
Electricity consumption	3.15 Kw/24h
Energy efficiency class	B
Frequency	50 Hz
Maximum room temperature	43 °C
Net weight	151 kg
Operating temperature	-2 +8 °C
Refrigerant gas	R290
Refrigeration	ventilated
Thermostat	Dixell/Carel
Voltage	230 V

Standard equipment

Included	1 Door grille