Cod: 76591445064

Static-chamber cooler with sliding doors, -22 to -12 °C, 101.5 × 63.5 × 89 (h) cm, 300 litres



Description

Why buy it?

Choosing this **static well cooler** means investing in a practical, reliable product with a functional design, perfect for your storage needs.

Key features

- **Optimal storage**: thanks to the **static cooling** system, your products remain at a stable and uniform temperature, ideal for preserving their quality.
- **Ease of use**: the **sliding glass doors** offer quick and easy access, even in confined spaces, minimising temperature loss.
- **Robust and functional design**: the **double-glazed tempered glass** ensures greater strength and thermal insulation, guaranteeing a long service life.
- **Uncompromising mobility**: thanks to the **4 castors**, 2 of which are fitted with brakes, you can easily move the cooler and lock it in place when necessary.
- **Intuitive control**: the **digital display** allows you to monitor and adjust the temperature precisely, ensuring maximum control.
- **Sustainability and safety**: the use of **R290 refrigerant**, which is environmentally friendly and efficient, minimises the environmental impact.

Technical specifications

- **External dimensions**: 101.5 x 63.5 x 89h cm
- **Internal dimensions**: 89 x 51.5 x 64.5h cm
- **Capacity**: 300 litres
- **Operating temperature**: from -12 °C to -22 °C
- **Refrigerant**: R290 (environmentally friendly)
- **Energy efficiency class**: D
- **Power consumption**: 0.12 kW
- **Noise** level: 52 dB
- **Weight**: 62 kg
- **Cooling system**: Static
- **Doors**: Sliding glass doors with double-glazed tempered glass
- **Defrosting**: Manual
- **Display**: Digital temperature control
- **Castors**: 4 castors, 2 of which are fitted with brakes

Dimensions

External dimensions	1015x635x890 mm
Internal dimensions	890x515x645 mm
Packaging dimensions	1100x750x860 mm

Technical specifications

Capacity	300 Lt

Defrosting	manual
Electrical Power	0.12 kW
Energy efficiency class	D
Net weight	62 kg
Noise levels	52 db
Operating temperature	-12 -22 °C
Refrigerant gas	R290
Weight including packaging	70 kg