Cod: 76591446065

Static-chamber cooler with sliding doors, -22 to -12 °C, 130.5 × 63.5 × 89 (h) cm, 400 litres



Description

Why buy it?

Choosing this **static well cooler** means investing in a practical, reliable product with a functional design, perfect for your storage needs.

Key features

- **Optimal storage**: thanks to the **static cooling** system, your products remain at a stable and uniform temperature, ideal for preserving their quality.
- **Ease of use**: the **sliding glass doors** offer quick and easy access, even in confined spaces, minimising temperature loss.
- **Robust and functional design**: the **double-glazed tempered glass** ensures greater strength and thermal insulation, guaranteeing a long service life.
- **Uncompromising mobility**: thanks to the **4 castors**, 2 of which are fitted with brakes, you can easily move the cooler and lock it in place when necessary.
- **Intuitive control**: the **digital display** allows you to monitor and adjust the temperature precisely, ensuring maximum control.
- **Sustainability and safety**: the use of **R290 refrigerant**, which is environmentally friendly and efficient, minimises the environmental impact.

Technical specifications

- **External dimensions**: 130.5 x 63.5 x 89h cm
- **Internal dimensions**: 118 x 51.5 x 64.5h cm
- **Capacity**: 400 litres
- **Operating temperature**: from -12 °C to -22 °C
- **Refrigerant**: R290 (environmentally friendly)
- **Energy efficiency class**: D
- **Power consumption**: 0.14 kW
- **Noise** level: 54 dB
- **Weight**: 75 kg
- **Cooling system**: Static
- **Doors**: Sliding glass doors with double-glazed tempered glass
- **Defrosting**: Manual
- **Display**: Digital temperature control
- **Castors**: 4 castors, 2 of which are fitted with brakes

Dimensions

External dimensions	1304x635x863 mm
Internal dimensions	1180x515x645 mm
Packaging dimensions	1400x750x860 mm

Technical specifications

Capacity	400 Lt

Defrosting	manual
Electrical Power	0.14 kW
Energy efficiency class	D
Net weight	65 kg
Noise levels	54 db
Operating temperature	-12 -22 °C
Refrigerant gas	R290
Weight including packaging	80 kg

Standard equipment

Included	3 baskets