Ristoattrezzature®

Cod: 8851101001007

Stainless steel refrigerated display cabinet with two glass doors, energy-efficient, 1,335 litres, ventilated, 0–8 °C



Description

1,335-litre stainless steel refrigerator with glass doors, compliant with catering standards. Internal and external structure in AISI 304 stainless steel. Rear panel and motor compartment in galvanised steel. ‘Embraco’ compressor rated for tropical conditions up to +43°C. “Dixell” digital thermostat. “EBM” forced-air cooling. Corrosion-resistant evaporator. Fitted with braked castors. Door fitted with a security lock. LED interior lighting. Glass door with integrated LED lighting. Automatic defrost. Rounded internal corners for easy cleaning. Self-closing door. Magnetic seals, easy to clean and replace. Insulation with 50 and 6 cm layers of high-efficiency foam. Compatible with GN sizes. Shelves mounted on rails. Shelves, rails and feet available as accessories.

Dimensions

External dimensions	1382x805x2112 mm
Grid dimensions	618x622 mm
Insulation thickness	60 mm
Internal dimensions	1260x640x1525 mm
Packaging dimensions	1436x860x2165 mm

Technical specifications

Capacity	1335 Lt
Compressor	Embraco EM2X3121U
Defrosting	air defrost
Electrical Power	0.35 kW
Electricity consumption	3.99 Kw/24h
Energy efficiency class	B
Frequency	50 Hz
Maximum room temperature	43 °C
Net weight	220 kg
Operating temperature	0 +8 °C
Refrigerant gas	R290
Refrigeration	ventilated
Thermostat	Dixell/Carel
Voltage	230 V

Weight including packaging	245 kg

Standard equipment

Included	4 Door grilles