Ristoattrezzature®

Cod: 8879102001010

Stainless steel dual-temperature refrigerated cabinet with 2 doors, low energy consumption, 840 litres, ventilated, -2 to +8 °C / -22 to -17 °C



Description

High-quality AISI stainless steel dual-temperature cabinet, 840 litres. Internal and external structure in stainless steel. Rear panel and motor compartment in galvanised steel. “Dixell” digital thermostat. “EBM” forced-air cooling. Corrosion-resistant evaporator. Wheels with brakes supplied as standard. Door fitted with a security key. Automatic defrost. Rounded internal corners for easy cleaning. Self-closing door. Magnetic seals, easy to clean and replace. Shelves mounted on hooks. Shelves, runners and feet available as accessories.

Dimensions

External dimensions	1200x730x1820 mm
Grid dimensions	510x525 mm
Insulation thickness	50 mm
Internal dimensions	1100x540x1380 mm
Packaging dimensions	1255x790x2000 mm

Technical specifications

Capacity	840 Lt
Compressor	Embraco EMTE2134U, Hua Yi HYB81MHUa
Defrosting	air defrost, hot gas
Electrical Power	0.87 kW
Electricity consumption	8.22 Kw/24h
Energy efficiency class	D
Frequency	50 Hz
Net weight	158 kg
Operating temperature	-2 +8, -22 -17 °C
Refrigerant gas	R290, R600A
Refrigeration	ventilated
Thermostat	Dixell/Carel
Voltage	230 V
Weight including packaging	170 kg

Standard equipment

Included	3 Door grilles