Cod: 88840040071604

Energy-efficient stainless steel refrigerated display counter with back panel, 4 doors, -2 to +8 °C, 223 × 60 × 85h cm



Description

Stainless steel tables for professional kitchens are essential in any catering business. To complete the fit-out of your premises, you can choose from a range of models and optional extras: let us help **you find the one that best suits your needs**.

The **4-door refrigerated table with a 10** cm**splashback for patisseries and kitchens** is the ideal piece of professional equipment for the catering sector. **Practical, spacious and durable**. The 10 cm**splashback** is a **useful** feature **for preventing food from splashing or falling onto the back of the table**.

Our catering table ensures **food is stored correctly**; it is built to **the highest quality standards** and is characterised by **low energy consumption**. Make way for the ideal product – make way for quality!

Design and operation

The **4-door refrigerated table for patisseries** helps you optimise your time and workspace. The **attention to detail** and**choice of materials** guarantee long-lasting quality.

The Ristoattrezzature **refrigerated counter for catering measures 223 x 60 x 85h cm** and offers a **total capacity of 390 litres**. Designed to meet the day-to-day needs of those working in the catering sector.

It stands out for:

- **Minimalist design**
- Highly professional**technical design**
- **Stainless steel construction**
- **4 doors** with an automatic closing system
- **Adjustable steel feet**.

The **magnetic seals** fitted to each door are **easy to clean and replace**. The **6 cm insulation thickness** makes all the difference to the quality of freezing.

The **handy** front-mounted **display** allows you to monitor the operating temperature, which you can easily set between **-2° and +8 °C**.

The **forced-air cooling system**, meanwhile, ensures the internal temperature remains constant at all times. The**tropicalised unit** can operate without issues at external temperatures of up to 43°C and a humidity level of 60 per cent.

The 4-door refrigerated display cabinet for patisseries and kitchens is also fitted with a **defrost** system designed to simplify the defrosting process: automatic, periodic and rapid, ensuring excellent long-term performance and consistent maintenance of the equipment.

The **anti-corrosion condensate evaporation** system will preserve the organoleptic qualities of the stored food.

Finally, the **refrigerant used is R290a**: a pure hydrocarbon (HC), considered environmentally friendly due to its low environmental impact. Used in industrial and commercial refrigeration, you can easily find it at any refrigeration specialist.

Why this is the right product for you

The **4-door refrigerated display counter with upstand for restaurants** serves a dual purpose:

- **storing food at low temperatures**
- providing**an excellent worktop**.

One of the main reasons you'll choose our 4-door refrigerated table is its **versatility** and **ability to optimise space**

, offering no fewer than 4 useful compartments that can be further subdivided using **33 x 45.5 cm shelves**.

This layout is particularly useful in **patisseries, cafés, pizzerias and catering establishments in general**.

By choosing our table, you'll ensure a comfortable working environment in just a few simple steps and you'll benefit from:

- **durability**
- **high performance**
- **low energy consumption**
- **environmental friendliness**.

Read the technical specifications for product details.

Dimensions

External dimensions	2230x600x850 mm
Grid dimensions	330x455 mm
Height of the splashback	100 mm
Insulation thickness	60 mm
Internal dimensions	1692x470x580 mm
Packaging dimensions	2285x655x985 mm

Technical specifications

Capacity	390 Lt
Compressor	Embraco EM2X3121U
Defrosting	air defrost
Electrical Power	0.4 kW
Electricity consumption	2.59 Kw/24h
Energy efficiency class	B
Frequency	50 Hz
Maximum room temperature	43 °C
Net weight	139 kg
Operating temperature	-2 +8 °C
Refrigerant gas	R290
Refrigeration	ventilated
Thermostat	Dixell/Carel
Voltage	230 V
Weight including packaging	173 kg

Standard equipment

Included	1 Door grille