Ristoattrezzature®

Cod: 88840030071608

Energy-efficient, tropicalised stainless steel refrigerated counter with back panel and 3 doors – -2 to +8 °C, 201×80×84h cm



Description

Energy-efficient refrigerated display cabinet with containers compliant with catering regulations. Internal and external structure in stainless steel. ‘Embraco’ compressor rated for tropical conditions up to +43°C. ‘Dixell’ digital thermostat. ‘EBM’ forced-air cooling. Corrosion-resistant evaporator. Automatic defrost. Adjustable steel feet included as standard. Rounded internal corners for easy cleaning. Self-closing door. Magnetic seals, easy to clean and replace. Compatible with GN sizes. 7 door rails included. Castors available as accessories.

Dimensions

External dimensions	2010x800x840 mm
Grid dimensions	400x600 mm
Height of the splashback	100 mm
Insulation thickness	60 mm

Technical specifications

Capacity	375 Lt
Compressor	Embraco EM2X3121U
Defrosting	air defrost
Electrical Power	0.4 kW
Electricity consumption	2.26 Kw/24h
Energy efficiency class	B
Frequency	50 Hz
Maximum room temperature	43 °C
Net weight	267 kg
Operating temperature	-2 +8 °C
Refrigerant gas	R290
Refrigeration	ventilated
Thermostat	Dixell/Carel
Voltage	230 V

Standard equipment

Included	7 guides per door leaf