Ristoattrezzature®

Cod: 95560971737016

Single-door, ventilated stainless steel refrigerated cabinet with touchscreen control, 900 litres, 79 × 102 × 209h cm, -2 to +8 °C



Description

The refrigerated cabinet features the following characteristics: - a monocoque body with 7.5 cm of HFO polyurethane foam insulation, which has a GWP of 0; - all materials used are AISI 304 both inside and out, with the exception of the top, back and external base, which are made of AISI 430; - monobloc units using R290 gas (GWP of 3), resulting in significant energy savings; - hot gas defrosting, rather than electric heating, saves energy and ensures faster defrosting; - partially ducted ventilation to ensure proper air circulation inside the cold room; - the runners feature folded, hand-protecting edges, with removable racks; - the fan stop switch activated when the door is opened is mechanical and does not need to be adjusted if the door's opening direction is changed; - the door is reversible; simply fit the lower hinge to the opposite side; - the interior fittings are interlocking and easily removable to ensure maximum convenience during cleaning; - in ventilated cabinets, the air outlet is protected by a duct, which ensures that the cold air flowing out is not obstructed by products or ice build-up;

Dimensions

External dimensions	790x1020x2090 mm

Technical specifications

Electrical Power	0.4 kW
Energy efficiency class	B
Frequency	50 Hz
Operating temperature	-2 +8 °C
Power supply	Electric
Voltage	230 V

Standard equipment

Included	16 LEVELS WITH 'L'-SHAPED RAILS, WITHOUT GRIDS, FOR BAKING TRAYS OR WORKTOPS MEASURING 600 X 800, SPACED 75 APART