Cod: 983600202332

Countertop refrigerated display cabinet, 70.2 × 56.8 × 68.6 (h) cm, with straight black glass on all four sides, 120 litres, 0 +12 °C



Description

The countertop refrigerated display cabinet is a particularly useful**piece of equipment for bars, patisseries and delicatessens** .

Easy to install and move, the refrigerated display cabinet **keeps your food at the right temperature and showcases it to customers**. Access is quick and easy, streamlining service by making the best use of counter space.

This model is black with straight-sided glass panels, ideal for any type of premises.

Design and operation

The **exclusive, minimalist and modern design** of **the 120-litre countertop refrigerated display cabinet** makes it suitable for any type of interior. Its clean lines do not compromise the available space and allow for thorough cleaning.

The structure is made of toughened glass, high-gloss stainless steel and plexiglass. Each material is selected for its ability to withstand the constant demands of professional environments. **The stainless steel ensures maximum resistance to abrasions and stains**, whilst the **toughened glass provides maximum visibility and excellent temperature retention**. The **dimensions of the refrigerated display cabinet are 70.2 x 56.8 x 68.6h cm,** with a **weight of 60 kg**.

The interior lighting uses cool-light LEDs to minimise energy consumption and prevent the products from overheating. Every detail of your preparations will be clearly visible and showcased thanks to the panoramic view provided by the glass panels and the diffused light.

The rear doors are sliding, allowing the operator to open and close them with ease.

Inside **,** the professional refrigerated **display** cabinet is fitted with **adjustable shelves, lined with PVC** to ensure a secure surface. One shelf measures **63 x 32 cm** and the other **63 x 35 cm**. The **adjustable feet** fitted to this bar-style refrigerated display cabinet can be adjusted to suit your working requirements. **The display cabinet is electrically powered with a power rating of 0.16 kW and a voltage of 230 V**. The operating temperature is adjustable between **0** and **+12 °C** via **a digital thermostat**. The **compressor is built-in** and ensures extremely low noise levels.

Cleaning and maintenance

The 120-litre countertop refrigerated display cabinet from Ristoattrezzature features **automatic defrosting**. This feature ensures consistently optimal performance and saves time on maintenance.

The display cabinet is made of multiple materials, so different cleaning products must be used. **For the toughened glass, use a microfibre cloth** dampened with a specific cleaning product or a mixture of water and vinegar.

Stainless steel should be cleaned with a mild detergent and without abrasive sponges to avoid damaging the protective coating. It is advisable to dry the plexiglass parts thoroughly to prevent streaks.

Why this is the right product for you

Choose this product to **ensure your food is as visible as possible** thanks to the large glass surface area. Our professional countertop refrigerated display cabinet is versatile and practical to use: it guarantees **excellent performance whilst keeping energy consumption low**.

Classified as **energy class B**, the display case consumes just **790 kWh per year**, allowing you to save on your energy bills whilst also reducing harmful emissions.

The refrigerant used in this unit is **R290**, a **100% natural** refrigerant that offers excellent thermodynamic performance and is environmentally friendly.

Choose a **product that is attractive, efficient and sustainable**: buy the catering refrigerated display cabinet that meets your needs online, or contact us for assistance.

Dimensions

External dimensions	702x568x686 mm
Packaging dimensions	755x620x720 mm

Technical specifications

Capacity	120 Lt
Defrosting	automatic
Electrical Power	0.16 kW
Energy efficiency class	B
Frequency	50 Hz
Net weight	57 kg
Operating temperature	0 +12 °C
Power supply	Electric
Refrigerant gas	R290
Refrigeration	ventilated
Voltage	230 V
Weight including packaging	60 kg

Standard equipment

Included	LED interior lighting and 2 removable, adjustable plastic-coated shelves (630 x 320 mm and 630 x 350 mm)