Cod: 93140022258011

2-door stainless steel refrigerated counter, -2 to +8 °C, 136×60×85h cm – FC



Description

Refrigerated display counter with a built-in, removable unit for easy maintenance; a circular flow of cold air designed so that it does not come into direct contact with the product; electronic temperature control with a digital thermostat; an electric heating element around the door frame to remove condensation; automatic defrosting with an electric heating element and automatic defrost temperature control, automatic evaporation of condensate water, and an anti-corrosion-treated evaporator. Door with return spring; door seal removable without tools; base with rounded corners; doors easily interchangeable with two- and three-drawer units; drawers easily removable with stainless steel telescopic runners. Height-adjustable stainless steel feet and the option to position the unit against a wall.

Dimensions

External dimensions	1360x600x850 mm
Insulation thickness	60 mm
Internal dimensions	900x430x560 mm
Packaging dimensions	1390x630x880 mm

Technical specifications

Capacity	159 Lt
Defrosting	electric defrost
Electrical Power	0.275 kW
Energy efficiency class	C
Frequency	50 Hz
Net weight	94 kg
Operating temperature	-2 +8 °C
Power supply	Electric
Refrigerant gas	R600A
Refrigeration	ventilated
Voltage	230 V
Weight including packaging	109 kg

Standard equipment

Included	2 grids measuring 33x43 cm and 2 pairs of rails