Cod: 1045100209975

Stainless steel dual-temperature refrigerated cabinet with 2 separate doors, 1,400 litres, -2 +10°C / -10 -22°C



Description

The product is constructed entirely from AISI 304 stainless steel with solid doors, and features two separate compartments, each with a net capacity of 625 litres. The left-hand side has an operating temperature range of -2 to +10°C, whilst the right-hand side has a range of -10 to -22°C. As the product has two operating temperature ranges, it has two energy efficiency classes. Energy efficiency class for positive temperatures: C; energy efficiency class for negative temperatures: F.

General features:

- 2/1 Gastronorm cabinets with a depth of 81.5 cm
- interior with rounded corners and moulded base
- 7.5 cm insulation made from eco-friendly polyurethane
- racks (5.2 cm pitch) and AISI 304 stainless steel runners
- forced-air cooling with an evaporator treated with anti-corrosion paint
- easily replaceable monobloc refrigeration unit
- Solid-door models with SN-T class condensing unit (max +43°C)
- R290 (propane) refrigerant
- Energy Saving electronic control panel with HACCP function
- Temperature alarm and dirty condenser alarm management
- ‘Overcooling’ rapid cooling function
- option to set high or low humidity
- automatic hot gas defrost
- serial port for connection to monitoring systems
- Automatic condensate evaporation via hot gas pipe
- internal lighting
- key-operated lock
- self-closing doors with 105° latch
- easily replaceable magnetic seals
- height-adjustable stainless steel feet (13–20 cm)

N.B.: To claim the Industry 4.0 tax credit, select the Wi-Fi option.

. 100% Made in Italy.

Dimensions

External dimensions	1500x815x2080 mm
Packaging dimensions	1540x880x2235 mm

Technical specifications

Amperage	4.98 A
Capacity	1400 Lt
Cooling capacity	0.999 kW

Defrosting	automatic
Electrical Power	0.8 kW
Energy efficiency class	C
Frequency	50 Hz
Net capacity	1250 Lt
Net weight	245 kg
Operating temperature	-10 -22, -2 +10 °C
Power supply	Electric
Refrigerant gas	R290
Refrigeration	ventilated
Voltage	230 V
Weight including packaging	265 kg

Standard equipment

Included	3 GN2/1 plastic-coated racks with stainless steel guides for each door