Cod: 1045200106374

85 cm deep dual-temperature refrigerated cabinet in stainless steel, 1 unit with 2 separate doors, 700 litres, -2 +10°C / -2 +10°C



Description

The product is constructed entirely from AISI 304 stainless steel with solid-panel doors and two separate compartments, each with a capacity of 300 litres. Both the upper and lower compartments have an operating temperature range of -2 to +10°C.

General features:

- 2/1 Gastronorm cabinets, 85 cm deep
- interior with rounded corners and moulded base
- 7.5 cm layer of eco-friendly polyurethane insulation
- racks (5.2 cm pitch) and AISI 304 stainless steel runners
- forced-air cooling with an evaporator treated with anti-corrosion paint
- easily replaceable buffer refrigeration unit
- Solid-door models with SN-T class condensing unit (max +43°C)
- R290 (propane) refrigerant
- Energy Saving electronic control panel with HACCP function
- Temperature alarm and dirty condenser alarm management
- ‘Overcooling’ rapid cooling function
- option to set high or low humidity
- Automatic defrosting with heating element
- serial port for connection to monitoring systems
- Automatic condensate evaporation with self-regulating heating element
- internal lighting
- key-operated lock
- self-closing doors with a 105° stop
- easily replaceable magnetic seals
- height-adjustable stainless steel feet (13–20 cm)

N.B.: To claim the Industria 4.0 tax credit, select the Wi-Fi option.

. 100% Made in Italy.

Dimensions

External dimensions	750x850x2080 mm
Packaging dimensions	770x880x2235 mm

Technical specifications

Amperage	3 A
Capacity	700 Lt
Cooling capacity	0.64 kW
Defrosting	automatic

Electrical Power	0.62 kW
Energy efficiency class	B
Frequency	50 Hz
Net capacity	600 Lt
Net weight	162 kg
Operating temperature	-2 +10 °C
Power supply	Electric
Refrigerant gas	R290
Refrigeration	ventilated
Voltage	230 V
Weight including packaging	174 kg

Standard equipment

Included	2 GN2/1 plastic-coated racks with stainless steel guides for each door