**Cod: 1045200106375**

# 85 cm deep dual-temperature refrigerated cabinet in stainless steel, 1 unit with 2 separate doors, 700 litres, -2 to +10°C / -10 to -22°C



## Description

The product is constructed entirely from AISI 304 stainless steel with solid-panel doors and two separate compartments, each with a capacity of 300 litres. The upper compartment has an operating temperature of 2–10°C, whilst the lower compartment has an operating temperature of –10 to –22°C. As the product has two operating temperature ranges, it has two energy efficiency classes. Energy efficiency class for the positive temperature range: B; energy efficiency class for the negative temperature range: E.

General features:

- 2/1 Gastronorm cabinets, 85 cm deep
- interior with rounded corners and moulded base
- 7.5 cm insulation made from eco-friendly polyurethane
- racks (5.2 cm pitch) and AISI 304 stainless steel runners
- forced-air cooling with an evaporator treated with anti-corrosion paint
- easily replaceable buffer refrigeration unit
- Solid-door models with SN-T class condensing unit (max +43°C)
- R290 (propane) refrigerant
- Energy Saving electronic control panel with HACCP function
- Temperature alarm and dirty condenser alarm management
- ‘Overcooling’ rapid cooling function
- option to set high or low humidity
- Automatic defrosting with heating element
- serial port for connection to monitoring systems
- Automatic condensate evaporation with self-regulating heating element
- internal lighting
- key-operated lock
- self-closing doors with a 105° stop
- easily replaceable magnetic seals
- height-adjustable stainless steel feet (13–20 cm)

**N.B.: To claim the Industry 4.0 tax credit, select the Wi-Fi option.**

. 100% Made in Italy.

## Dimensions

| | |
|---|---|
| External dimensions | 750x850x2080 mm |
| Packaging dimensions | 770x880x2235 mm |

## Technical specifications

| | |
|---|---|
| Amperage | 4 A |
| Capacity | 700 Lt |
| Cooling capacity | 0.63 kW |

| | |
|---|---|
| Defrosting | automatic |
| Electrical Power | 0.69 kW |
| Energy efficiency class | B |
| Frequency | 50 Hz |
| Net capacity | 600 Lt |
| Net weight | 167 kg |
| Operating temperature | -10 -22, -2 +10 °C |
| Power supply | Electric |
| Refrigerant gas | R290 |
| Refrigeration | ventilated |
| Voltage | 230 V |
| Weight including packaging | 179 kg |

**Standard equipment**

| | |
|---|---|
| Included | 2 GN2/1 plastic-coated racks with stainless steel guides for each door |