Cod: 1045200331974

85 cm deep dual-temperature refrigerated cabinet in stainless steel, 3 doors, 2300 litres, -2 to +10°C / -2 to +10°C



Description

The product is constructed entirely from AISI 304 stainless steel with solid-panel doors, and features two separate compartments, one with a capacity of 1,365 litres and the other 625 litres. Both the left and right compartments have an operating temperature range of -2 to +10°C. As the product has two operating temperature ranges, it has two energy efficiency classes. Energy efficiency class for positive temperatures: C; energy efficiency class for negative temperatures: D.

General features:

- 2/1 Gastronorm cabinets, 85 cm deep
- interior with rounded corners and moulded base
- 7.5 cm layer of eco-friendly polyurethane insulation
- racks (5.2 cm pitch) and AISI 304 stainless steel runners
- forced-air cooling with an evaporator treated with anti-corrosion paint
- easily replaceable buffer refrigeration unit
- Solid-door models with SN-T class condensing unit (max +43°C)
- R290 (propane) refrigerant
- Energy Saving electronic control panel with HACCP function
- Temperature alarm and dirty condenser alarm management
- ‘Overcooling’ rapid cooling function
- option to set high or low humidity
- Automatic defrosting with heating element
- serial port for connection to monitoring systems
- Automatic condensate evaporation with self-regulating heating element
- internal lighting
- key-operated lock
- self-closing doors with a 105° stop
- easily replaceable magnetic seals
- height-adjustable stainless steel feet (13–20 cm)

N.B.: To claim the Industria 4.0 tax credit, select the Wi-Fi option.

. 100% Made in Italy.

Dimensions

External dimensions	2250x850x2080 mm
Packaging dimensions	2290x880x2235 mm

Technical specifications

Amperage	3.73 A
Capacity	2300 Lt
Cooling capacity	1.12 kW
Defrosting	automatic

Electrical Power	0.6 kW
Energy efficiency class	C
Frequency	50 Hz
Net capacity	1990 Lt
Net weight	335 kg
Operating temperature	-2 +10 °C
Power supply	Electric
Refrigerant gas	R290
Refrigeration	ventilated
Voltage	230 V
Weight including packaging	357 kg

Standard equipment

Included	3 GN2/1 plastic-coated racks with stainless steel guides for each door