Cod: 10967063001012

Stainless steel refrigerated freezer cabinet, 1-door, 700 litres, ventilated, -18 to -22°C – TE



Description

700-litre freezer cabinet, -18/-22°C, 1 stainless steel door. This low-temperature freezer cabinet has a temperature control range from -18° to -22°C.

Key features:

• Front-mounted electronic control panel for adjusting and setting the temperature using 2 NTC sensors

• Cooling is provided by a removable monobloc refrigeration unit, operating with R452A gas

• Forced-air cooling

• The refrigeration unit is tropicalised as standard (ambient temperature +40°C and relative humidity of 60%) and guarantees excellent performance even in particularly hot environments.

• Defrosting and condensate drainage are fully automatic

• The structure is made from AISI 304 stainless steel for both the interior and exterior, with the exception of external parts such as the ceiling, rear panel and base, which are made from galvanised steel.

• The insulation is 6 cm thick, with a core of high-pressure polyurethane injected without CFCs, which are harmful to the environment

• The internal corners of the chamber are rounded to allow for easy and safe cleaning

• The door is 6 cm thick and features an automatic closing mechanism with a magnetic seal to ensure a perfect seal

• The door is reversible for opening from right to left; this can be arranged retrospectively by ordering a special kit (on request), or by specifying the door reversal when placing the order.

• The adjustable feet are made of stainless steel and can be adjusted in height within a range of 110 to 19h cm

. 100% Made in Italy.

Dimensions

External dimensions	710x809x2034 mm
Insulation thickness	60 mm
Packaging dimensions	760x840x2090 mm

Technical specifications

Capacity	700 Lt
Defrosting	automatic
Electrical Power	0.47 kW

Energy efficiency class	D
Frequency	50 Hz
Maximum room temperature	40 °C
Net capacity	596 Lt
Net weight	99 kg
Operating temperature	-18 -22 °C
Power supply	Electric
Refrigerant gas	R452A
Refrigeration	ventilated
Testing	+43 / 65% °C/RH
Voltage	230 V
Weight including packaging	109 kg

Standard equipment

Included	3 sets of hooks, 3 GN 2/1 plastic-coated racks, fan retainer and door-edge heating element