Cod: 112190021722016

2-burner gas hob with pilot light, cast-iron hob and 28.2 kW gas oven, 80×70×85h cm



Description

2-burner gas hob with cast-iron hotplates and gas oven, stainless steel body. Press-formed, double-walled oven door with a sturdy handle. Knobs made from thermosetting plastic.

Thick cast-iron hob with rounded corners, cast in a single piece. Removable central round insert. Central circular stainless-steel burner, suitable for high-temperature operation. Maximum temperature of approximately 500°C at the hottest central point, gradually decreasing towards the edges through zones of varying isothermal conditions.

Heating is provided by sealed burners with a stabilised, overlapping crown flame, available in different power ratings (6.2 kW and 8.5 kW).

Each burner is fitted with a safety gas valve that allows the output to be adjusted from maximum to minimum. Safety is ensured by a thermocouple powered by the pilot burner’s flame.

Hob grids and burners made from RAAF matt-enamelled cast iron, resistant to alkalis, acids and fire.

Hob grids are positioned on a moulded base with rounded edges to ensure ease of cleaning and protect against spilt liquids.

Moulded stainless steel drip pans with rounded edges are positioned beneath the burners and can be easily removed for cleaning.

2/1 GN gas oven. Removable stainless steel oven rack. Oven base made of thick steel and reinforced with a series of ribs.

Insulation of the cooking chamber and oven door is provided by a layer of high-temperature-resistant ceramic fibre.

Rapid temperature rise and heat retention are achieved thanks to a high-efficiency, stabilised-flame burner with an integrated diffuser, suitable for operation at high temperatures.

The oven burner is fitted with a thermostatic safety gas valve that allows the temperature to be adjusted up to 300°C. Safety is ensured by a thermocouple powered by the burner flame.

Laser-cut worktop finish to ensure a ‘butt-joint’ fit between worktops and a secure fixing of the worktops to one another.

Height-adjustable stainless steel feet.

Testing carried out using natural gas or LPG, depending on the user’s requirements.

. 100% Made in Italy.

Dimensions

External dimensions	800x700x850 mm

Technical specifications

Burner Power	6 (x1) kW, 6.2 (x1) kW, 8.5 (x1) kW
Gas Power	28.2 kW
Net weight	130 kg

Power supply	Gas