Cod: 87090708

Refrigerated display cabinet with curved glass, 631 litres, 0+8°C, 170×75×135h cm



Description

Ristoattrezzature's **professional refrigerated display cabinet**, constructed from **AISI 430 stainless steel** with **AISI 304 stainless steel** profiles, is a piece of equipment designed to meet the needs of **patisseries**, **supermarkets**, snack bars, sushi bars and all those businesses that need to serve their customers chilled delicatessen products such as sandwiches, ready-made salads, fruit platters, pastries and cakes, sushi and much more.

The **ventilated refrigerated display cabinet**, featuring internal LED lighting and a capacity of 600 litres, is fitted with three adjustable internal shelves and curved panoramic glass panels to showcase the display areas inside: the glass is double-layered and toughened to ensure effective maintenance of the positive temperature, adjustable between 0 and +8°C via a digital control. The rear double-glazed sliding door makes opening and closing the display unit extremely convenient.

Commissioning the refrigerated display cabinet

Before putting the unit into operation following delivery, we recommend leaving it switched off for at least 6 hours, switching it on and waiting for it to reach the desired temperature; only then should you place food and drink inside.

What is refrigeration?

Refrigeration is a method of food preservation that involves keeping products at a low temperature without freezing the water contained within the food. To achieve this, food is kept at a temperature ranging from 0°C to 10°C. As well as temperature, the storage environment must also be taken into account, particularly humidity: an unsuitable environment can lead to undesirable consequences such as the loss of the product's characteristics, the growth of harmful microorganisms, or wilting or browning. Keeping the interior of the appliances perfectly clean will ensure proper air circulation within the compartments or on the walls, which is essential for the appliances to function correctly.

Dimensions

External dimensions	1700x750x1350 mm

Technical specifications

Amperage	5 A
Capacity	631 Lt
Compressor	secop dle 12.6 mn
Electrical Power	0.95 kW
Energy efficiency class	D
Frequency	50 Hz
Net weight	255 kg
Operating temperature	0 +8 °C
Power supply	Electric

Refrigerant gas	R290
Refrigeration	ventilated
Shelves	3 Nr
Thermostat	Dixell/Carel
Voltage	230 V

Standard equipment

Included	3 grills in total