Ristoattrezzature®

Cod: 113570060242855

Refrigerated display cabinet for patisserie, straight-sided glass, ventilated, remote motor, white, +2 to +6 °C, 222.7 × 94 × 106.4 (h) cm



Description

Key strengths:

- ‘Made in Italy’ technology, design and manufacturing;
- Compact dimensions (depth of just 94.5 cm);
- Ideal for any type of setting;
- Low energy consumption and low environmental impact;
- Stainless steel worktop and display shelves;
- Easily removable stainless steel display trays to ensure easy cleaning of the display cabinet;
- Front and side panels that are easily removable and customisable;
- Hot-air anti-fogging system for the glass;
- White pre-painted sheet metal base (suitable for food contact with high-pressure injected polyurethane insulation free from hazardous CFC gases (density 40 kg/m³);
- Can be recessed;
- Quick and easy installation.
- Sheet metal side panels with a tempered glass side;
- Electronic control panel;
- Ceiling light with LED lighting;
- 2 open compartments, complete with a middle shelf;
- Condensate evaporation tray fitted with a PTC heating element.

Dimensions

External dimensions	2227x940x1064 mm

Technical specifications

Climate class	3
Cooling capacity	1.03 kW
Exhibition space	1.40 Mq
Frequency	50 Hz
Operating temperature	+2 +6 °C
Power consumption (standard specification)	0.023 kW
Power consumption of the lighting (standard fit)	0.023 kW
Power supply	Electric
Refrigerant gas	R452A

Refrigeration	ventilated
Voltage	220 V, 240 V