**Cod: 113570360242860**

# Refrigerated display cabinet for patisserie, with straight glass panels, ventilated, remote motor and 2 blue intermediate shelves, +2 to +6 °C, 180.2 × 94 × 138.4h cm



## Description

Key strengths:

- ‘Made in Italy’ technology, design and manufacturing;
- Compact dimensions (depth of just 94.5 cm);
- Ideal for any type of setting;
- Low energy consumption and low environmental impact;
- Stainless steel worktop and display shelves;
- Easily removable stainless steel display trays to ensure easy cleaning of the display cabinet;
- Front and side panels that are easily removable and customisable;
- Hot-air anti-fogging system for the glass;
- White pre-painted sheet metal base (suitable for food contact with high-pressure injected polyurethane insulation free from hazardous CFC gases (density 40 kg/m³);
- Can be recessed;
- Quick and easy installation.
- Sheet metal side panels with a tempered glass side;
- Electronic control panel;
- Ceiling light with LED lighting;
- 2 open compartments, complete with a middle shelf;
- 2 intermediate tempered glass shelves;
- Condensate evaporation tray fitted with a PTC heating element.

## Dimensions

| | |
|---|---|
| External dimensions | 1802x940x1384 mm |

## Technical specifications

| | |
|---|---|
| Climate class | 3 |
| Cooling capacity | 0.83 kW |
| Exhibition space | 1.67 Mq |
| Frequency | 50 Hz |
| Operating temperature | +2 +6 °C |
| Power consumption (standard specification) | 0.020 kW |
| Power consumption of the lighting (middle shelf) | 0.032 kW |
| Power consumption of the lighting (standard fit) | 0.016 kW |
| Power supply | Electric |

| | |
|---|---|
| Refrigerant gas | R452A |
| Refrigeration | ventilated |
| Voltage | 220 V, 240 V |