Cod: 11443002016

7-tray GN 1/1 electric combi oven with steam convection and touch-screen controls – AT



Description

Key features:

- Humidity control with an automatic vapour retention/ejection system;

- Door with triple-glazed, low-emissivity tempered glass. Easy to clean;

- 25.4 cm thermally insulated capacitive HD display with simple, intuitive graphics;

- Hinges made entirely from stainless steel. High-quality materials, long service life;

- Wi-Fi connection with remote monitoring and diagnostics via iOS/Android app;

- Programmable automatic washing system with integrated compartments for detergent and rinse aid. Retractable spray arm included;

- Smart Cooking function that continuously and automatically monitors the cooking chamber, ensuring the highest level of performance;

- Full control over cooking modes: manual cooking, core temperature monitoring, timer-controlled cooking, delta T cooking, cooking and keep-warm;

- Maximised energy efficiency and absolute temperature uniformity within the cooking chamber;

- Each motor has an integrated encoder with speed differential monitoring and capacitive fault detection. Fans with 8 speeds and integrated reverse function;

- Option to synchronise the start or end times for all baking trays;

- Core temperature probe, with 4 measurement points for optimised cooking monitoring;

- User-friendly recipe book. Option to select pre-set recipes and/or add your own;

- The high level of insulation in the cooking chamber and flue, combined with the use and engineering of advanced fans for heat extraction, and superior-quality components, protects all oven models from damage caused by high temperatures, ensuring unprecedented levels of efficiency and longevity.

Dimensions

Distance between baking trays	68 mm
External dimensions	786x870x888 mm
Packaging dimensions	870x970x1030 mm

Technical specifications

Amperage	26 A
Baking tray capacity	7 Jan 1/1
Baking tray load capacity	18 Kg
Frequency	50/60 Hz
Maximum load	126 Kg
Net weight	120.8 kg
Operating temperature	+30 +260 °C
Power supply	Electric
Pressure	2 - 3 bar
Rated power	13.1/15.5 kW
Room capacity	100 litres
Voltage	380 V, 415 V
Water resistance rating	IPX4
Weight including packaging	154.4 kg

Standard equipment

Included	Flushing system and multi-point heart probe