Cod: 115780030062975

Stainless steel refrigerated table, 3-door, +2 +8 °C, 179.5 × 70 × 85h cm, monobloc - FC



Description

Why buy it?

If you're looking for a refrigerated table that combines **functionality, durability and efficiency**, this 3-door model is the ideal choice. Designed for intensive use in professional settings such as restaurants, pizzerias, delis and patisseries, it offers **ample stainless steel work surfaces** and generous internal capacity, whilst always keeping your ingredients at the perfect temperature. What's more, its **ease of use** and **low maintenance** make it a valuable everyday ally.

Key features

- **Ventilated cooling for an even temperature**
  The **forced-air cooling** system ensures even distribution of cold air throughout the interior compartment. This means that every item of food, regardless of its position, maintains the same ideal temperature for storage.
- **Precise control with a digital thermostat**
  The **digital thermostat** allows you to set the desired temperature precisely between **+2 and +8 °C**, enabling constant and accurate control, which is essential for ensuring freshness and food safety.
- **Prevention of condensation thanks to the electric heating element on the doors**
  The **integrated electric heating element on the doors** prevents condensation from forming, even in conditions of high humidity or when the doors are opened frequently. This keeps the interior of the cabinet dry and hygienic at all times.
- **Automatic defrosting for easy maintenance**
  The **automatic defrost** system simplifies the management of the refrigerated counter, reducing the time spent on maintenance and ensuring optimal performance at all times without the need for manual intervention.
- **Corrosion-resistant evaporator**
  The evaporator, treated with an anti-corrosion coating, extends the equipment's service life by protecting the internal components from wear caused by moisture and corrosive agents.
- **Monobloc refrigeration unit with plug-in system**
  The **monobloc refrigeration unit**, made from plastic with **high thermal insulation**, is designed to offer maximum energy efficiency and ease of installation thanks to the practical **plug-in** system.
- **Doors with return springs for secure closure**
  The **doors with return springs** close automatically, preventing accidental loss of cold air and improving energy efficiency.
- **Doors with versatile and practical drawer units**
  The table can be configured with **drawer units featuring 2 or 3 drawers**, thus offering maximum versatility in organising the interior space.
  The **telescopic runners** ensure smooth and full opening of the drawers, making it easy to access even items stored at the very back.

Technical specifications

- **External dimensions:** 179.5 x 70 x 85h cm
- **Internal dimensions:** 133.5 x 53 x 56h cm
- **Capacity:** 417 litres
- **Operating temperature:** +2/+8 °C
- **Maximum ambient temperature:** 35 °C
- **Cooling:** ventilated
- **Defrosting:** automatic
- **Refrigerant:** R600A
- **Energy efficiency class:** D
- **Power consumption:** 0.275 kW
- **Voltage:** 230 V
- **Frequency:** 50 Hz
- **Material:** stainless steel
- **Net weight:** 108 kg
- **Gross weight:** 128 kg

- **Insulation thickness:** 6 cm

Standard equipment

- **3 GN1/1 racks**
- **3 pairs of rails** for positioning the racks

Dimensions

External dimensions	1795x700x850 mm
Insulation thickness	60 mm
Internal dimensions	1335x530x560 mm
Packaging dimensions	1825x730x880 mm

Technical specifications

Capacity	417 Lt
Defrosting	automatic
Electrical Power	0.275 kW
Energy efficiency class	D
Frequency	50 Hz
Material	stainless steel
Maximum room temperature	35 °C
Net weight	108 kg
Operating temperature	+2 +8 °C
Power supply	Electric
Refrigerant gas	R600A
Refrigeration	ventilated
Voltage	230 V
Weight including packaging	128 kg

Standard equipment

Included	3 GN1/1 racks and 3 pairs of rails