Cod: 11579063007001

Stainless steel refrigerated cabinet, 1 door, 700 litres, 0–+8 °C, ventilated, monobloc – FC



Description

Ventilated refrigeration – built-in unit – evaporator concealed to maximise available space – motor compartment with insulated side panels – electronic temperature control with digital thermostat - electric heating element around the door frame to prevent condensation – automatic defrosting – electronic control of defrost temperature – automatic evaporation of condensation water – evaporator treated for corrosion resistance. Door with return spring and reversible hinge (except G-GNV600DT) – key-operated door lock – door seal removable without tools – internal LED light – base with rounded corners – external base and rear panels in galvanised sheet metal. Height-adjustable feet. The M-GN models are fitted with a monobloc refrigeration unit – a plug-in refrigeration assembly characterised by quick and easy installation or removal/replacement – quieter motor – monobloc protected by a stainless steel sheet.

Dimensions

External dimensions	740x830x2010 mm
Insulation thickness	60 mm
Internal dimensions	620x700x1396 mm
Packaging dimensions	765x855x2080 mm

Technical specifications

Capacity	700 Lt
Defrosting	automatic
Electrical Power	0.305 kW
Energy efficiency class	D
Frequency	50 Hz
Material	stainless steel
Maximum room temperature	38 °C
Net capacity	650 Lt
Net weight	108 kg
Operating temperature	0 +8 °C
Power supply	Electric
Refrigerant gas	R290
Refrigeration	ventilated
Voltage	230 V

Weight including packaging	123 kg

Standard equipment

Included	3 GN2/1 racks and 3 pairs of rails