Cod: 115800030023014

Three-phase conveyor-belt dishwasher with a capacity of 67–100 baskets per hour, dimensions 118 × 83 × 143 (h) cm



Description

Compact model. Specially designed for confined spaces.
2 speeds.

Stainless steel construction
Central feed mechanism in stainless steel fitted with a torque limiter via a clutch in the event of a blockage.
Separation of the various zones by means of intermediate screens.
Automatic start-up.

Economy

Flush water economiser.
Pressure reducer for regulating the rinse water flow.
Programmed automatic shutdowns when no load is present.
Stop and feed delay upon activation of the limit switch.

Cleaning and maintenance

Wide, power-assisted door, allowing access for cleaning and inspections.
Pipes and nozzles can be easily removed for cleaning.
Stainless steel filters.
Simple draining of the boiler by releasing the pipe.
Easy fault detection via indicator lights.
Easy repairs without removing the machine.

Washing

Flushing pipes with recessed stainless steel nozzles.
High-efficiency, durable nozzles that are not subject to wear and tear.
Powerful washing pump in a vertical position, allowing for self-draining.
Easy installation of the dosing unit, with a pre-fitted inlet in the tank. Rinsing
Removable rinse pipes with stainless steel diffusers offering high dispersion power.
Automatic boiler filling with no risk of heating element failure.
Temperature control via high-precision sensors.
Viewing and adjusting wash and rinse temperatures on the digital display at the touch of a button.
Easy installation of the dosing unit, with a pre-fitted inlet in the boiler.

Dimensions

Basket dimensions	500x500 mm
Clear height	400 mm
External dimensions	1180x830x1430 mm

Packaging dimensions	1250x950x1700 mm

Technical specifications

Boiler capacity	20 Lt
Frequency	50 Hz
Net weight	200 kg
Power supply	Electric
Pump power	1.5 kW
Voltage	400 V
Weight including packaging	239 kg