Cod: 11584002363017

Black ventilated refrigerated display counter for patisseries and sandwich shops, 0 +6 °C, 135×100×120h cm



Description

Why buy it?

This refrigerated display cabinet is designed for those who want to combine **modern design**, **advanced functionality** and **maximum product visibility**. Its black colour gives it an elegant look and makes it easy to integrate into any professional setting, whilst the fan-assisted cooling ensures even temperature distribution. Ideal for **patisseries, sandwich shops, cafés and food outlets**, it guarantees high performance and ease of use, showcasing every creation on display.

Key features

- **Ventilated cooling**
  Thanks to forced-air cooling technology, the display cabinet ensures an **even temperature distribution** across the entire display surface. This system is particularly suitable for keeping pastries, sandwiches and ready-to-eat items fresh without temperature fluctuations that would compromise their quality.
- **Digital temperature control**
  The intuitive **integrated digital display** allows you to precisely control the internal temperature, setting it within the optimal range of **0 to +6 °C**. This is an essential feature for complying with HACCP regulations and storing products safely and professionally.
- **Front glass panel with gas spring**
  The front glass panel opens easily thanks to the **gas spring** mechanism, facilitating cleaning, maintenance and the stocking of the display counter. A practical and hygienic solution that allows quick access to the display shelf, whilst maintaining an elegant and streamlined design.
- **Stainless steel display shelf and top**
  The **stainless steel** surfaces ensure **hygiene, durability and ease of cleaning** – essential features in any food environment. The top surface can also be used as a support surface for serving customers or for counter accessories.
- **Internal LED lighting**
  LED lighting highlights the products on display, enhancing their appearance and encouraging purchases. The light is uniform, energy-efficient and does not affect the internal temperature, ensuring maximum efficiency.
- **Rear sliding plexiglass doors**
  The rear sliding doors made of **transparent plexiglass** allow quick and easy access to the interior of the display cabinet, facilitating service and restocking without obstructing the customer's view from the front.

Technical specifications

- **External dimensions:** 135x100x120h cm
- Power**supply:** Electric
- **Climate class:** 3
- **Frequency:** 50/60 Hz
- **Refrigerant gas:** Environmentally friendly R290
- **Power consumption:** 0.71 kW
- **Cooling:** Ventilated
- **Operating temperature:** 0 to +6 °C
- **Voltage:** 230 V

Dimensions

External dimensions	1350x1000x1200 mm
Packaging dimensions	1450x1100x1400 mm

Technical specifications

Climate class	3
Electrical Power	0.71 kW
Frequency	50/60 Hz
Net weight	130 kg
Operating temperature	0 +6 °C
Power supply	Electric
Refrigerant gas	R290
Refrigeration	ventilated
Voltage	230 V
Weight including packaging	150 kg